SERVICE BODY BUYERS GUIDE WORK SHEET

This worksheet is provided to help you in the decision making process with the many options and features available.

Body

CA (Measurement from cab to center of rear axle) determines the body length.

❑ 72V	❑ 76V	❑ 80V	❑ 96	❑ 108	❑ 132	❑ SingleWheel
37.6" CA Ford Ranger Only	36.9" CA Dodge Only	❑ Chevy 42" CA ❑ Ford 40" CA	56" CA Single or Dual Wheel Check box at right See Page 9	60" CA Single or Dual Wheel Check box at right See Page 10	84" CA Dual Wheel Only Total of 8 Compartments See Page 11	48.5" Floor Width ❑ DualWheel 54.5" Floor Width
Single Wheel Vertical Configuration Only - See Page 8						

Compartments

Select compartment style and configuration



❑ Standard
❑ Low Profile
❑ Top Opening

(See Pages 2&3)



❑ V Configuration



❑ H Configuration



❑ VH Configuration



❑ HV Configuration

Service Body Standard Equipment is indicated below. Use the quantity column to indicate the number of additional items ordered and use the compartment columns to indicate placement.	Std.	Qty.	Front Compartment		Intermediate Compartment (Model 132 Only)		Horizontal Compartment		Rear Compartment	
			Street	Curb	Street	Curb	Street	Curb	Street	Curb
Divider Trays (2 in each front vertical compartment)	2									
Tray Dividers (20 standard)	20									
Shelves (1 shelf in each rear vertical compartment)	1									
Divider Tray (1 in horizontal compartment)	1									
Nested Slide Out Trays (150 or 250 lbs. capacity)										
Indicate number of trays & capacity (3, 4, or 5 tray sets)										
Book Rack										
Parts Cabinet										
Dual Gas Bottle Holder										
Drop Well For Gas Bottles w/ Vents In Doors										
Material Hooks										

Latch Options

Paddle Activated Rotary

❑ Stainless Finish

One-Point "T" Latch

❑ Stainless Finish

Three-Point "T" Latch

❑ Stainless Finish

Stylized Black Nylon Rotary Paddle Latch

❑ Black Latch

Note: "T" Latch is standard equipment on all front raised compartment doors and dual vertical overlapping doors

Electro-Mechancial Door Lock (EML)

❑ Yes ❑ No (See Page 6)

Master Locking System

❑ Yes ❑ No (See Page 6)

Bumper Options

Bumper Style

❑ Standard
❑ Hinged Recessed Cover
❑ Recessed Ball Hitch Plate
❑ Recessed
❑ Recessed Lights

Bumper Surface Textures

❑ Standard Treadplate
❑ Grip Strut
❑ Grip Punch

Note: Chose one bumper style and one surface texture.

(See Page 4)

High Roof (See Page 5)

Floor to Ceiling Heights

❑ 54" ❑ 60" ❑ 72"

HiRoof Options

❑ Sliding Roof
❑ Skylight Windows
❑ Doorsin sides for exterior access
❑ DomeLights with rear mounted switch
❑ Extrainterior shelving
❑ Fullyenclosed interior storage compartments with interior access doors.
❑ Windowguards for bulkhead and rear windows
❑ Slidingglass in bulkhead window
❑ Hotstick box with access door

Treadplate Overlays

❑ Steel
❑ Aluminum
❑ Compartment Tops
❑ CompartmentRear End Panels
❑ Insideof Load Space
❑ InsideFront
❑ ScuffPlate
❑ FrontCompartment Rock Panel
❑ Insideof Tailgate

(See Page 6)

This work sheet does not include every option available.

If you have special needs, discuss them with your Omaha Standard Distributor to custom tailor a body that fits your specific needs.

Ladder Racks

❑ Adjustable Overhead
❑ Sloping Top Mounted
❑ HiRoofAdjustable Overhead
❑ HiRoofSide Mounted
❑ Standard Compartment Top Rack
❑ LadderRack Guide Rails
❑ LadderRack Guide Rollers
❑ SpringLoaded Hold Downs
❑ QuickRemoval Brackets

(See Page 7)

Made in the U.S.A.

Matches Or Exceeds Truck Manufacturers' Warranties

6 YEAR LIMITED WARRANTY Hinges, Latches, Trays and Rust Through

3 YEAR LIMITED WARRANTY All Other Body Components